Non-contact optical control of multiple particles and defects using holographic optical trapping with phase-only liquid crystal spatial light modulator

Suman Anand^{a, b}, Rahul P. Trivedi^a, Gabriel Stockdale^a, Ivan I. Smalyukh^{a,*} ^a Department of Physics, University of Colorado at Boulder, Colorado 80309-0390, USA
^b A mity Institute of Nanotachnology, Amity University, Noide, Utter Predech 201201, Ind ^bAmity Institute of Nanotechnology, Amity University, Noida, Uttar Pradesh 201301, India

ABSTRACT

In this work, three-dimensional manipulation of multiple defects and structures is performed in the framework of holographic optical trapping approach using a spatial light modulator. A holographic optical tweezers system is constructed using a liquid crystal spatial light modulator to generate multiple optical traps. We optimize the tweezers setup to perform polarization-sensitive holographic optical trapping and then explore properties of optical trapping in thermotropic liquid crystals and compare them to the case of isotropic fluids. One of the major challenges complicating the quantitative measurements in these fluids is the anisotropic nature of the liquid crystal medium, which makes the tight focusing of the laser beam difficult and considerably weakens optical trapping forces. Using liquid crystals with low birefringence allows us to mitigate these artefacts. Optical trapping forces and the trap stiffness are first calibrated for different laser powers using viscous drag forces. This is then used to probe inter-particle and defect-particle interaction forces as well as to characterize tension of line defects in the bulk of liquid crystals.

Keywords: Optical tweezers, micro-manipulation, multiple traps, liquid crystals, spatial light modulator (SLM), CGH (computer generated holograms), holography, disclination

1. INTRODUCTION

Non-contact optical control is of great interest for many areas of science and technology as it can allow one to manipulate objects spanning from single atoms to microscopic particles. Soon after the demonstration of a single beam optical technique for trapping micrometer-sized transparent dielectric particles suspended in a fluid medium [1], the soqalled optical tweezers permeated research in the biological and condensed matter physical sciences. In biology, the

scma.1()]TJ-5.8, ddinndefo4.7152 0D.006 Tc7392 T025 OTJ- spane case ong ofogrbTJchnolondicrospush-24.3188 -6707 TD.006 Tc..0

Emerging Liquid Crystal Technologies IV, edited by Liang-Chy Chien, Ming Hsien Wu, Proc. of SPIE Vol. 7232, 723208 · © 2009 SPIE · CCC code: 0277-786X/09/\$18 · doi: 10.1117/12.807873

In order to achieve this, two telescopes are included in the optical train of the HOT setup, one before, and the other after the SLM. The first 2.5:1 telescope arrangement is used to expand the laser beam from 5.0 mm to 12.0mm in order to overfill the active area of the SLM. It consists of two

solution at the edge of the cover slide of this cell next to the channel; the cell is then self-filled due to the action of capillary forces. The typical concentration of polystyrene spheres in the deionized water is kept below 0.01wt%. The LC cells are assembled from glass plates coated with polyvinyl alcohol (obtained from Alfa Aesar) alignment layers buffed to set the uniform in-plane far-field director \hat{n} . The thickness of the LC cell is set at 30-60 μ m using UV-curable adhesive with the dispersed appropriately sized glass spacers. The samples are prepared using low-birefringence (n~0*.04*) nematic LC ZLI-2806 having the average refractive index of \sim 1.49 (n_o= 1.48 and n_e= 1.52 are ordinary and extraordinary refractive indices, respectively)*.* To obtain the cholesteric LC, ZLI-2806 is doped with a chiral additive CB15 (obtained from Merck). For the FCPM studies, the LCs are doped with ~0.01wt% of the fluorescent dye N, N'-Bis(2,5-di-tertbutylphenyl)-3,4,9,10-per

3.2 In-plane spatial calibration

For the in-plane spatial calibration, we use the Arryx HOTgui software and calibrate distances as needed for the holographic optical trapping. There are two calibration procedures that we perform by using 60X microscope objective: Ruler Calibration and HOT calibration. Ruler calibration allows

3.4 Trapping depth calibration

A cell filled with deionized water containing 2μm polystyrene spheres is used for the trapping depth calibration. A single trap is created using the software. When a polystyrene sphere is brought close to the trap, it experiences the influence of optical forces, eventually hops towards the trap and becomes spatially-localized, i.e., its Brownian motion is ceased. If the sphere is trapped in the beam but appears out of focus,

maximum laser trapping force for a given laser power (for such estimates, one can assume that $\eta_{eff} \approx \alpha_4 = 57cP$, i.e., equal to the average viscosity of ZLI 2806 at 20°C). The escape velocity measurements were performed along two mutually orthogonal paths, one parallel and the other perpendicular to the rubbing direction of the alignment layer. We observe directional anisotropy of the viscous drag forces, Fig. 7, which is related to the anisotropy of \mathcal{A}

In general, the optical trapping forces in the LCs (e.g. ZLI-2806) are somewhat weaker as compared to the forces acting on the particles of the same size dispersed in water (partially due to the fact that the difference between the refractive index of the particle and the surrounding medium is larger in the case of water) but still sufficiently strong to enable robust laser manipulation. Fig. 10 illustrates the holographic optical trapping and manipulation of 4 m MR particles in the bulk of the cholesteric LC of pitch about 5 microns using the SLM-based HOT setup.

4.2. Three-dimensional trapping of multiple colloids

Figure 11 shows the movement of multiple 2 m polystyrene spheres in water along the optical axis. The sequence of images shown therein demonstrates that the spheres can be programmed to move in different groups while being trapped at different depths in the vertical direction, along the microscope's optical axis. All the six spheres trapped in the outer ring of Fig 11(a) are co

Downloaded from SPIE Digital Library on 25 Mar 2012 to 128.138.65.186. Terms of Use: http://spiedl.org/terms

Downloaded from SPIE Digital Library on 25 Mar 2012 to 128.138.65.186. Terms of Use: http://spiedl.org/terms

experiments. Although the field-induced propagation [32] and deformation [33] dynamics of disclinations allow one for a limited spatial manipulation of these defects, this can be done only at certain boundary conditions. Robust approaches to manipulate defects are in a great demand and the conventional laser tweezers with polarization control have already been successfully used for this purpose [30].

In this work, we demonstrate that the defect lines can be also manipulated by using handles in the form of particle optically trapped and manipulated with the HOT setup. Fig. 15 (a-e) shows manipulation of a topologically stable disclination using a trapped MR particle with tangential surface anchoring. The particle is slowly pulled in the direction perpendicular the defect line using a laser trap generated with the HOT. Since the particle motion across the defect is resisted because of incompatibility of the surface boundary conditions at the particle's surface and the molecular alignment within the defect core, the defect line can be stretched similar to an elastic string. Figure 15 (a-d) demonstrates that the defect line is moved and bent around the particle using optical tweezers. Using a trap and optical trapping force of the order of 10 pN, we have moved the particle for a distance of ~100 microns along the defect line as shown in Fig. 15 (a-e). After such manipulation, the particle is strongly pinned to the defect line and trapping force of the order of 50- 70pN had to be used in order to detach the particle from the defect line while leaving this defect line essentially intact. The defect line was found to straighten (in order to minimize its total energy) and return to its original position after the particle was separated from it. By stretching the defect line with a colloidal particle and balancing the laser trapping force with the defect line tension [16] one can also measure tension of defect lines. Similarly to the case of such experiments performed with time-shared laser traps, calibrated HOT setup also gives values of defect line tension in the range of 10-100pN, as expected.

One of the most commonly observed textures of the cholesteric LCs is the texture containing oily streaks (vide.0069 ni

17e). Thus, manipulation of defect lines with trapped colloidal particles allows one to test topological stability of LC defect lines.

5. CONCLUSIONS

We have constructed the holographic laser trapping system integrated with a fluorescence confocal microscope that is optimized for polarization-sensitive 3D trapping and imaging of director structures, defects, and colloidal particles in the LC media and other anisotropic fluids. We have provided examples of the simultaneous multiple-particle manipulation at different depths of the LC and isotropic fluid samples. We also show feasibility of 3D manipulation of defects and testing of their topological stability using the holographic optical trapping approach. The combined 3D imaging and trapping in LCs and LC colloidal suspensions further expands the manipulation and imaging capabilities available for the study of these intriguing anisotropic media.

ACKNOWLEDGEMENT

We acknowledge the support of the Institute for Complex Adaptive Matter (ICAM), International Institute for Complex Adaptive Matter (I2CAM) and the NSF grants no. DMR 0645461, DMR-0820579 and DMR-0847782 & the University of Colorado Innovation Seed Grant award. We also wish to express our thanks for discussions held with Dennis Gardner, Dr. Clayton Lapointe, Dr. Taewoo Lee, Dr. Pratibha Ramarao, and Dr. Andrij Trokhymchuk. We are also thankful to the representatives of BNS (Anna Linnenberger) and Arryx (Pamela Korda) for technical assistance.

REFERENCES

- ^[1] Ashkin, A., Dziedzic, J. M., Bjorkholm, J. E., and Chu, S., "Observation of a single-beam gradient force optical trap for dielectric particles," Optics Letters $11(5)$ 288-290 (1986)
- ^[2] Schutze, K., Becker, I., Becker, K. F., Thalhammer, S., Stark, R., Heckl, W. M., Bohm, M., and Posl, H., "Cut out or poke in - the key to the world of single genes: Laser micromanipulation as a valuable tool on the look-out for the origin of disease," Genetic Analysis-Biomolecular Engineering 14(1) 1-8 (1997).
- Schutze, K., Posl, H., and Lahr, G., "Laser micromanipulation systems as universal tools in cellular and molecular biology and in medicine," Cellular and Molecular Biology $44(5)$ 735 (1998).
- f^{4]} Korda, P. T., Spalding, G. C., and Grier, D. G., "Evolution of a colloidal critical state in an optical pinning potential landscape," Physical Review B $66(024504)$ (2002).
- [5] Ashkin, A., "Optical trapping and manipulation of neutral particles using lasers," Proceedings of the National Academy of Sciences of the United States of America 94(10) 4853-4860 (1997).
- [6] Ashkin, A., "History3(r)m4m optical prsapp pry3(r)m and,mani

Downloaded from SPIE Digital Library on 25 Mar 2012 to 128.138.65.186. Terms of Use: http://spiedl.org/terms